



KI	\mathbf{O}	OP	LE	D 1	8"
					ı

Suspended, architectural LED 'ring' providing uplight and downlight. Great for lobbies and modern office spaces. Available suspended with cable/canopy up to 48". Custom colors available.

PROJECT: _	
TYPE:	



Features

- · Glare-free lighting
- · Custom Colors and Outputs Available
- Damp Location Rated
- CRI Value: 80+; available in 90+
- 5 year, 50,000 hour lamp life Warranty
- 3000k and 3500k color temperatures available

Applications

- Offices
- Lobbies
- · Retail Stores
- Reception Areas
- Corridors

LED System Information

	Nominal System Watts	Nominal Delivered Lumens	Nominal Efficacy
Standard (LTG1)	22W	2090Lm	95Lm/W
Low (LTG2)	17W	1600Lm	95Lm/W
High (LTG3)	27W	2525Lm	93Lm/W

<u>Please Note:</u> Standard CRI is 80+, must specify for requests over 90. Outputs reflected in chart based on 3500K color temperature. For custom LED package requests consult factory; wattages vary based on specified output. Additional photometric information available.

Details

Construction: Die formed and embossed, heavy gauge cold rolled steel housing. Spun steel trim.

NOTES:


Optics: Custom molded opal lens.

Electrical: Integral driver with dimming. Driver remote with 'FC' (flat canopy) option.

Warranty: 5 year limited warranty; covers standard components.

Approvals: Union made and ETL listed. Rated for Damp Location.

Extrusion Dimensions



Ordering Information

KLOOP LED Series 18" Size 18"

LTG1- Standard LTG2- Low LTG3- High C- Custom Output (ie-C3500Lm)

O System Color Temp 31- Standard 3000K 32- Low 3500K

3000K 3500K Voltage 120 277 UNV AC Mounting
AC- Air Craft Cable (adjusts up to 48")

DB
Driver
DB- Standard 10% Dimming (0-10V)

Options
EM-Emergency Pack
(Driver Remote)
FC- Flat Canopy
(Driver Remote)

90CRI- CRI of 90+

Ordering Example: KLOOP LED-18"-LTG1-4000K-UNV-AC-DB-EM

December 2018