



KI	OOP	I FD	3FT

Suspended, architectural LED 'ring' providing uplight and downlight. Great for lobbies and modern office spaces. Available suspended with cable/canopy up to 48". Custom colors available.

PROJECT: _	
TYPE:	 



#### **Features**

- · Glare-free lighting
- · Custom Colors and Outputs Available
- Damp Location Rated
- CRI Value: 80+; available in 90+
- 5 year, 50,000 hour lamp life Warranty
- 3000k and 3500k color temperatures available

## **Applications**

- Offices
- Lobbies
- Retail Stores
- Reception Areas
- Corridors

# **LED System Information**

	Nominal System Watts	Nominal Delivered Lumens	Nominal Efficacy
Standard (LTG1)	32W	3,150Lm	95Lm/W
Low (LTG2)	27W	2,525Lm	95Lm/W
High (LTG3)	42W	3,900Lm	93Lm/W

<u>Please Note:</u> Standard CRI is 80+, must specify for requests over 90. Outputs reflected in chart based on 3500K color temperature. For custom LED package requests consult factory; wattages vary based on specified output. Additional photometric information available.

#### **Details**

**Construction:** Die formed and embossed, heavy gauge cold rolled steel housing. Spun steel trim.

NOTES: \_

Optics: Custom molded opal lens.

**Electrical:** Integral driver with dimming. Driver remote with 'FC' (flat canopy) option.

Warranty: 5 year limited warranty; covers standard components.

Approvals: Union made and ETL listed. Rated for Damp Location.


### **Extrusion Dimensions**

AC

AC- Air Craft Cable

(adjusts up to 48")

Mounting



### **Ordering Information**

**KLOOP LED System** Voltage LED Size Color Temp 3FT LTG1- Standard 3000K 120 Series LTG2- Low 3500K 277 LTG3- High UNV C- Custom Output

(ie-C3500Lm)

- DB
Driver
DB Standard 10% Dimming (0.10%)

**DB**- Standard 10% Dimming (0-10V)

EM-Emergency Pack (Driver remote) FC- Flat Canopy (Driver remote) 90CRI- CRI of 90+

**Options** 

Ordering Example: KLOOP LED-3FT-LTG1-4000K-UNV-AC-DB-EM

December 2018