


DATE	PROJECT	FIRM	TYPE
------	---------	------	------



Architectural luminaire with very low profile. LED luminaire that provides continuous downlight regardless of length. Custom outputs and colors available.

FEATURES

- Available In Custom Lengths & Long Runs To 1/16" Accuracy
- Optional 'Power Over Wire' System
- Corners & Patterns Available (See Page 2)
- 100% Downlight
- Damp Location Rated
- CRI 90+ Standard
- 2700K, 3000K, 3500K, and 4000K Color Temperatures Available
- Rated Life- 100,000 hours at L70; 50,000 hours at L90

APPLICATIONS Offices, Reception Areas & Corridors

CONSTRUCTION Extruded Aluminum Housing With Die Cast Aluminum End Caps | **OPTICS** Acrylic Diffuse Lens with no LED Imaging


WARRANTY 5 Year Limited Warranty (Covers Standard Components) | **FINISH** Standard Powder-Coated White. Custom RAL Colors Available

FIXTURE RATINGS & CERTIFICATIONS Union Made ETL Listed | Made In The USA Damp Location Rated



ELECTRICAL 0-10V Remote Driver with 10% Dimming. **Optional 'Power Over Wire'** Eliminates Power Feed Cord by Combining the Aircraft Cable and Power Feed. 0-10 1% Dimming Driver also available.

EXTRUSION DIMENSIONS



*Please Note: Fixture depth is 1-3/4" when using 'ACP' Option

LED SYSTEM INFORMATION

	Nominal System Watts	Nominal Delivered Lumens
Standard (LTG1)	5.25 W/ft	315 Lm/ft
Low (LTG2)	3.5 W/ft	210 Lm/ft
High (LTG3)	7.25 W/ft	400 Lm/ft

Based on a 3500K luminaire using one driver. Please consult factory for custom lumen outputs & wattage.

ORDERING

1 - FIXTURE ID KUSH LED DN	2 - LENGTH 4 - 4 ft 8 - 8 ft x'-x" - Custom (specify length)	3 - COLOR TEMP 27 - 2700K/90 CRI 30 - 3000K/90 CRI 35 - 3500K/90 CRI 40 - 4000K/90 CRI	4 - LED SYSTEM LTG1 - Standard LTG2 - Low LTG3 - High C - Custom Output (ie-C550Lm/ft)	5 - VOLTAGE UNV - Universal (120/277V)	6 - DRIVER (Remote) DB - Standard 10% Dimming (0-10V) DB1% - 1% Dimming (0-10V) DB.01% - .01% Dimming (0-10V) LTEA - Lutron 2-wire 1% Dimming L3DA - Lutron 3-wire 1% Dimming LDE1 - Lutron Digital EcoSystem LDE5 - 5 Series EcoSystem; 5% Dimming DMX - DMX Control
--------------------------------------	--	---	---	--	--

**Patterns available consult factory

7 - FINISH W - White (Standard) CC - Custom Color (provide RAL#)	8 - MOUNTING AC - Aircraft Cable (50") SM - Surface Mount ACP - Power Over Aircraft Cable	9 - CIRCUIT (Optional) EM 120V - Emergency Pack EM 277V - Emergency Pack
---	---	---


DATE	PROJECT	FIRM	TYPE
------	---------	------	------

CORNERS & PATTERNS


Available with illuminated corners, angles, and custom patterns. **Must consult factory for custom corners and patterns.**




Square Patterns



T Patterns




Custom Angles



Custom Patterns


ACP- 'Power Over Aircraft Cable' Option:

*PLEASE NOTE: EXTRUSION IS 1-3/4" TALL WHEN USING ACP OPTION



DATE	PROJECT	FIRM	TYPE
------	---------	------	------


PHOTOMETRICS



KUSH LED DN 4FT LTG1 3500K
 DELIVERED LUMENS: 1,785Lm
 TOTAL WATTS: 21W

ZONAL LUMEN SUMMARY


ZONE	LUMENS	% LAMP	% FIXTURE
0.00 - 30.00	558.53	17.68	31.27
0.00 - 40.00	891.18	28.21	49.90
0.00 - 60.00	1494.22	47.29	83.67
0.00 - 90.00	1785.87	56.52	100.00
90.00 - 120.00	0.51	0.02	0.03
90.00 - 150.00	0.51	0.02	0.03
90.00 - 180.00	0.51	0.02	0.03
0.00 - 180.00	1785.87	56.52	100.00



KUSH LED DN 4FT LTG2 3500K
 DELIVERED LUMENS: 1,199Lm
 TOTAL WATTS: 14W

ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LAMP	% FIXTURE
0.00 - 30.00	373.85	17.65	31.17
0.00 - 40.00	597.45	28.21	49.82
0.00 - 60.00	1003.62	47.38	83.69
0.00 - 90.00	1199.26	56.62	100.00
90.00 - 120.00	0.37	0.02	0.03
90.00 - 150.00	0.37	0.02	0.03
90.00 - 180.00	0.37	0.02	0.03
0.00 - 180.00	1199.26	56.62	100.00



KUSH LED DN 4FT LTG3 3500K
 DELIVERED LUMENS: 2,341Lm
 TOTAL WATTS: 29W

ZONAL LUMEN SUMMARY

ZONE	LUMENS	% LAMP	% FIXTURE
0.00 - 30.00	732.33	17.70	31.27
0.00 - 40.00	1168.28	28.23	49.89
0.00 - 60.00	1960.57	47.37	83.72
0.00 - 90.00	2341.59	56.58	99.99
90.00 - 120.00	0.35	0.01	0.01
90.00 - 150.00	0.35	0.01	0.01
90.00 - 180.00	0.35	0.01	0.01
0.00 - 180.00	2341.93	56.59	100.00